



KAMAG 2400 ST

Self propelled

48	AXLE LINES (2 bogies/axle line)	
0	large powerpack	
Deadweight		
Trailers	:	216 t
Capacity per axle line	:	43,5 t
Net average load/axle line		5,3 t
Netto load		
Load	:	225 t
Supports	:	20 t
Total load	:	245 t
Gross Average load /axle line	:	9.6 t
Gross Average load /bogie	:	4.8 t
Gross Average load (projected)	:	2.8 t/m²

References:

Saddle & Heights:
DC-5301_transport saddle_final solution 29.06.2017.pdf

REV.	DATE	DESCRIPTION	DRAWN	VERIFIED	APPROVED
-	02/08/17	First Issue	W.D.K.	W.D.K.	P.D.B.

Copyright Sarens group. All rights reserved.

CLIENT:

TYPE: Transport Drawing

EQUIPMENT: 2x 24L Kamag 2400 ST

TITLE: Transport of DC530A/B (225t)

SCALE: 1/150 | SITE: Pancevo-Serbia

PROJ: | PROJECT: S-15-10443 | OWNER: SAR | STATUS: Concept

SIZE: A3 | DOC No: S-15-10443_DR0019 | SHEET: -

F:\projects\Serbia\Pancevo\CB&I\S-15-10443\valid\S-15-10443_DR0019.dwg, 02/08/2017 16:15:29